

Printing Multi Functional Devices imageRUNNER ADVANCE DX 717iZ / 617i

# imageRUNNER ADVANCE DX 717iZ / 617i



## Main Unit ^

<b>Machine Type</b>	A4 Monochrome Laser Multifunctional
<b>Core Function</b>	Print, Copy, Scan, Send and Optional Fax
<b>Processor</b>	Canon Dual Custom Processor (Shared)
<b>Control Panel</b>	25.6cm (10.1in) TFT LCD WSVGA Color Touch panel
<b>Memory</b>	Standard: 3.0GB RAM
<b>Hard Disk Drive</b>	Standard*1: 320GB (available disk space: 250GB)
<b>Interface Connection</b>	NETWORK Standard: 1000Base-T/100Base- TX/10Base-T, Wireless LAN (IEEE

	802.11 b/g/n) Optional: NFC, Bluetooth Low Energy
	OTHERS Standard: USB 2.0 x1 (Host) x 2, USB 3.0 (Host) x1, USB 2.0 (Device) x1 Optional: Copy Control Interface
<b>Paper Supply Capacity (A4, 80 g/m<sup>2</sup>)</b>	Standard: 650 Sheets  100-sheets Multi-purpose tray x1 550-sheets Paper cassette x1 Maximum: 3 300 Sheets (with High Capacity Cassette Feeding Unit-D1)
<b>Paper Output Capacity (A4, 80 g/m<sup>2</sup>)</b>	iR-ADV DX 617i: 500 sheets iR-ADV DX 717iZ: 1 000 sheets
<b>Finishing Capabilities</b>	iR-ADV DX 617i: Collate, Group iR-ADV DX 717iZ: Collate, Group, Offset* <sup>2</sup> , Staple
<b>Supported Media Types</b>	Multi-purpose tray: Thin, Plain, Recycled, Heavy, Color, Transparency, Bond, Envelope  Paper Cassette: Thin, Plain, Recycled, Heavy, Color, Labels, Bond, Pre-punched
<b>Supported Media Sizes (Standard)</b>	Multi-purpose tray: Standard size: A4, A5, A5R, A6, B5 Custom size: 76.2 x 127.0 mm to 216.0 x 355.6 mm Envelope: COM10 No.10, Monarch, DL, ISO-C5  Paper Cassette: Standard size: A4, A5, A5R, A6, B5 Custom size: 99.0 x 148.0 mm to 216.0 x 297.0 mm
<b>Supported Media Weights</b>	Multi-purpose tray: 60 to 199g/m <sup>2</sup> Cassettes: 60 to 135g/m <sup>2</sup> Duplex: 60 to 120g/m <sup>2</sup>
<b>Warm-up Time</b>	Quick Startup Mode: 4s or less* <sup>3</sup> From Sleep Mode: 10s or less From Power On: 10s or less* <sup>4</sup>
<b>Dimensions (W x D x H)</b>	iR-ADV DX 617i: 500 x 598 x 617 mm iR-ADV DX 717iZ: 502 x 598 x 814 mm

<b>Installation Space (W x D)</b>	Standard model / Finisher model: 1,052 x 823 mm (with left CRG door open + right door open + the cassette drawer open)
<b>Weight</b>	iR-ADV DX 617i: Approx. 37 kg including toner iR-ADV DX 717iZ: Approx. 46 kg including toner
<b>Print</b> <span style="float: right;">^</span>	
<b>Print Speed*<sup>5</sup> (pages per minute)</b>	iR-ADV DX 717iZ Up to 71 pages per minute (A4), Up to 113 pages per minute (A5), Up to 40 pages per minute (A5R, A6)  iR-ADV DX 617i Up to 61 pages per minute (A4), Up to 99 pages per minute (A5), Up to 35 pages per minute (A5R, A6)
<b>Print Resolution (dpi)</b>	600 x 600
<b>Page Description Languages</b>	Standard: UFR II, PCL6, Adobe® PostScript® 3™
<b>Direct Print</b>	Supported file types: TIFF, JPEG, PDF, EPS, and XPS
<b>Printing from Mobile and Cloud</b>	AirPrint, Mopria, Google Cloud Print, and Canon Business Print, and uniFLOW Online
<b>Fonts</b>	PS fonts: 136 Roman PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S/T* <sup>5</sup> (Japanese, Korean, Simplified and Traditional Chinese), Barcode fonts* <sup>6</sup>
<b>Operating System</b>	UFR II: Windows® 7 / 8.1 / 10 / Server2008 / Server2008 R2 / Server2012 / Server2012 R2 / Server2016 / Server2019, Mac OS X (10.10 or later)  PCL: Windows® 7 / 8.1 / 10 / Server2008 / Server2008 R2 / Server2012 / Server2012 R2 / Server2016 / Server2019  PS: Windows® 7 / 8.1 / 10 / Server2008 / Server2008 R2 / Server2012 / Server2012 R2 / Server2016 / Server2019, Mac OS X (10.10 or later)

PPD: Windows® 7 / 8.1 / 10, Mac OS X (10.9 or later)

## Copy

### Copy Speed\*7 (Black and White and Colour)

iR-ADV DX 717iZ  
Up to 71 pages per minute (A4), Up to 113 pages per minute (A5), Up to 40 pages per minute (A5R, A6)

iR-ADV DX 617i  
Up to 61 pages per minute (A4), Up to 99 pages per minute (A5), Up to 35 pages per minute (A5R, A6)

### First-Copy-Out Time (A4)

Approx. 5s or less

### Copy Resolution (dpi)

600 x 600

### Multiple Copies

Up to 9 999 copies

### Copy Density

Automatic or Manual (9 Levels)

### Magnification

Variable zoom: 25% to 400% (1% Increments)  
Preset reduction / enlargement: 25%, 50%, 70%, 81%, 86%, 100% (1:1), 115%, 122%, 141%, 200%, 400%

## Scan

### Standard Type

Single-pass Duplexing Automatic Document Feeder\*8 [2-sided to 2-sided (Automatic)]

### Document Feeder Paper Capacity (80g/m<sup>2</sup>)

Up to 100 Sheets

### Acceptable Originals and Weights

Platen: Sheet, Book, and 3-Dimensional Objects


Document Feeder media weight:  
1-sided scanning: 42 to 128g/m<sup>2</sup> (Black and White), 64 to 128g/m<sup>2</sup> (Colour)  
2-sided scanning: 50 to 128g/m<sup>2</sup> (Black and White), 64 to 128g/m<sup>2</sup> (Colour)

Note:  
Business card: 80 to 220g/m<sup>2</sup>  
Originals with width narrower than A6: 50 to 128g/m<sup>2</sup>

### Supported Media Sizes

Platen scanning size: up to 216.0 x 355.6 mm

Document feeder media size:  
A4, A5R, A6, B5

	<p>Custom size: 48.0 x 128.0 mm to 216.0 x 355.6 mm</p> <p>Business card: 48.0 x 85.0 mm to 55.0 x 91.0 mm</p>
<b>Scan Speed (images per minute: Black and White and Colour, A4)</b>	<p>SEND (300 x 300 dpi):</p> <p>Automatic Color Select "OFF":</p> <p>1-sided Scanning: 95</p> <p>2-sided Scanning: 190</p> <p>Automatic Color Select "ON":</p> <p>1-sided Scanning: 50</p> <p>2-sided Scanning: 100</p> <p>COPY (600 x 600 dpi):</p> <p>1-sided Scanning: 95</p> <p>2-sided Scanning: 140</p>
<b>Scan Resolution (dpi)</b>	<p>Scan for Copy: 600 x 600</p> <p>Scan for Send: (Push) 600 x 600 (SMB/FTP/WebDAV/IFAX), (Pull) 600 x 600</p> <p>Scan for Fax: 600 x 600</p>
<b>Pull Scan Specifications</b>	<p>Colour Network ScanGear2. For both TWAIN and WIA</p> <p>Supported OS: Windows®7/ 8.1/ 10/ Server2008/ Server2008 R2/ Server2012/ Server2012 R2/ Server 2016</p>
<b>Send</b> 	
<b>Destination</b>	<p>Standard: E-mail/Internet FAX (SMTP), SMB3.0, FTP, WebDAV, Mail Box</p> <p>Optional: Super G3 FAX, IP Fax</p>
<b>Address Book</b>	LDAP (2 000)/Local (1 600)/Speed dial (200)
<b>Send Resolution (dpi)</b>	<p>Push: up to 600 x 600</p> <p>Pull: up to 600 x 600</p>
<b>Communication Protocol</b>	<p>File: FTP(TCP/IP), SMB3.0 (TCP/IP), WebDAV</p> <p>E-mail/I-Fax: SMTP, POP3</p>
<b>File Format</b>	<p>Standard: TIFF, JPEG, PDF (Compact, Searchable, Apply policy, Optimize for Web, PDF A/1-b, Trace &amp; Smooth, Encrypted, Device Signature, User Signature), XPS (Compact, Searchable, Device Signature, User Signature), Office Open XML (PowerPoint, Word)</p>

## Fax



<b>Maximum Number of Connection Lines</b>	1
<b>Modem Speed</b>	Super G3: 33.6 kbps G3: 14.4 kbps
<b>Compression Method</b>	MH, MR, MMR, JBIG
<b>Resolution (dpi)</b>	400x400 (Ultra Fine), 200x400 (Super Fine), 200x200 (Fine), 200x100 (Normal)
<b>Sending / Receiving Size</b>	A4, A5* <sup>9</sup> , A6* <sup>9</sup> , B5* <sup>9</sup> / A4, A5, B5
<b>Fax Memory</b>	Up to 30 000 pages (2 000 jobs)
<b>Speed Dials</b>	Max. 200
<b>Group Dials / Destinations</b>	Max. 199 dials
<b>Sequential Broadcast</b>	Max. 256 addresses
<b>Memory Backup</b>	Yes

## Store



<b>Mail Box (Number supported)</b>	100 User Inboxes, 1 Memory RX Inbox, 50 Confidential Fax Inboxes
	Maximum 30,000 pages (2,000 jobs) stored
<b>Advanced Box</b>	Communication Protocol: SMB or WebDAV Supported Client PC: Windows® 8.1 / 10 Concurrent Connections (Max.): SMB:64, WebDAV:3
<b>Advanced Box Available Disc Space</b>	Standard: 16GB

## Security



<b>Authentication and Access Control</b>	User Authentication - Picture Login, Picture and PIN Login, Card Login, Username and Password Login, Function Level Login, Mobile Login
	Department ID Authentication - Department ID and PIN Login, Function Level Login
	uniFLOW Online Express - PIN Login, Picture Login, Picture and PIN Login, Card Login, Card and PIN Login, Username and Password Login,

	<p>Department ID and PIN Login, Function Level Login</p> <p>Access Management System - Access Control</p>
<b>Document Security</b>	<p>Print Security - Secure Print, Encrypted Secure Print, Forced Hold Printing, uniFLOW Secure Print<sup>*10</sup></p> <p>Receive Data Security - Confidential Fax Inbox Forwarding Received Documents Automatically</p> <p>Scan Security - Encrypted PDF, Device Signature PDF/XPS, User Signature PDF/XPS, Adobe LiveCycle® Rights Management ES2.5 Integration</p> <p>BOX Security - Mail Box Password Protected, Advanced Box Access Control</p> <p>Send Data Security - Setting for requesting password input per transmission, Restricted E-mail/File send functions, Confirming FAX number, Allow/Restrict Fax Driver Transmissions, Allow/Restrict Sending from History, S/MIME Support</p> <p>Document Tracking - Secure Watermark</p>
<b>Network Security</b>	<p>TLS 1.3, IPSec, IEEE802.1X authentication, SNMP V3.0, Firewall Functionality (IP/MAC Address Filtering), Dual Network Support (Wired LAN/Wireless LAN, Wired LAN/Wired LAN), Disabling Unused Functions (Enabling/Disabling Protocols/Applications, Enabling/Disabling Remote UI, Enabling/Disabling USB Interface), G3 FAX separation from LAN, USB Port separation from LAN, Prohibit the execution of files stored in Advanced Box in the MFP, Scan and Send -Virus Concerns for E-mail Reception</p>
<b>Device Security</b>	<p>Protecting HDD Data (HDD Data Encryption (FIPS140-2 Validated), HDD Data Overwrite Erase, HDD Lock), Standard HDD Initialize,</p>

	Trusted Platform Module (TPM), Job Log Conceal Function, Protecting MFD Software Integrity, Checking MFD Software Integrity (Verify System at Startup, Runtime Intrusion Detection) Optional: Comply IEEE2600.2 (Common Criteria Certification) (available at a later date)
<b>Device Management and Auditing</b>	Administrator Password, Digital Certificate And Key Management, Audit Log, Cooperating with External Security Audit System (Security Information and Event Management), Image Data Logging, Security Policy Setting
<b>Environmental</b> <span style="float: right;">^</span>	
<b>Operating Environment</b>	Temperature: 10 to 30°C Humidity: 20 to 80 % RH (Relative Humidity)
<b>Power Source</b>	220-240V, 50/60Hz, 4.8A
<b>Power Consumption</b>	Maximum: 1,500 W Standby: Approx. 28.92 W <sup>*11</sup> Sleep mode: Approx. 1.0 W <sup>*12</sup>
<b>Consumables</b> <span style="float: right;">^</span>	
<b>Toner Cartridge/s</b>	T03 Black
<b>Software and Printer Management</b> <span style="float: right;">^</span>	
<b>Tracking and Reporting</b>	Universal Login Manager (ULM) uniFLOW Online Express
<b>Remote Management Tools</b>	iW Management Console eMaintenance Content Delivery System
<b>Scanning Software</b>	Network ScanGear
<b>Optimisation Tools</b>	Canon Driver Configuration Tool
<b>Platform</b>	MEAP (Multifunctional Embedded Application Platform)
<b>Document Publishing</b>	iW Desktop



## Paper Supply Options



<b>Cassette Module-AG1</b>	<p>Paper Capacity: 550 sheets (80g/m<sup>2</sup>)</p> <p>Paper Type: Thin, Plain, Recycled, Heavy, Color, Labels, Bond, Pre-punched</p> <p>Paper Size: A4, A5, A5R, A6, B5, Custom size: 99.0 x 148.0 mm to 216.0 x 355.6 mm</p> <p>Paper Weight: 60 to 135g/m<sup>2</sup></p> <p>Power Source: From the Main Unit</p> <p>Dimensions (W x D x H): 484 x 450 x 127 mm (attached to the main unit)</p> <p>Weight: Approx. 7 kg</p>
<b>Envelope Cassette Module-A1</b>	<p>Paper Capacity: 75 sheets (Envelope)</p> <p>Envelope Size: COM10 No.10, Monarch, DL, ISO-C5</p> <p>Paper Weight: 80 to 100g/m<sup>2</sup></p> <p>Power Source: From the Main Unit</p> <p>Dimensions (W x D x H): 484 x 450 x 127 mm (attached to the main unit)</p> <p>Weight: Approx. 7 kg</p>
<b>Cassette Feeding Unit-AR1</b>	<p>Paper Capacity: 550 sheets (80g/m<sup>2</sup>)</p> <p>Paper Type: Thin, Plain, Recycled, Heavy, Color, Labels, Bond, Pre-punched</p> <p>Paper Size: A4, A5, A5R, A6, B5, Custom size: 99.0 x 148.0 mm to 216.0 x 355.6 mm</p> <p>Paper Weight: 60 to 135g/m<sup>2</sup></p> <p>Power Source: From the Main Unit</p> <p>Dimensions (W x D x H): 642 x 657 x 456 mm (attached to the main unit)</p> <p>Weight: Approx. 19 kg</p>
<b>High Capacity Cassette Feeding Unit-D1</b>	<p>Upper Cassette:</p> <p>Paper Capacity: 550 sheets (80g/m<sup>2</sup>)</p> <p>Paper Type: Thin, Plain, Recycled, Heavy, Color, Labels, Bond, Pre-punched</p> <p>Paper Size: A4, A5, A5R, A6, B5</p> <p>Custom size: 99.0 x 148.0 mm to 216.0 x 355.6 mm</p> <p>Paper Weight: 60 to 135g/m<sup>2</sup></p> <p>Lower Cassette:</p> <p>Paper Capacity: 2,100 sheets (80g/m<sup>2</sup>)</p>

Paper Type: Thin, Plain, Recycled,  
Heavy, Color, Bond, Pre-punched  
Paper Size: A4  
Paper Weight: 60 to 135g/m<sup>2</sup>  
Power Source: From the Main Unit  
Dimensions (W x D x H): 642 x 657  
x 456 mm (attached to the main  
unit)  
Weight: Approx. 27 kg

## Output Features <sup>\*13</sup>



### Finisher Model (iR-ADV DX 717iZ)

Tray Capacity (with 80g/m<sup>2</sup> paper,  
same paper type):  
Upper Tray: A4, A5R, B5: 400 sheets  
Lower Tray: A4, A5R, B5: 100 sheets  
Main unit output tray: A4, A5, A5R,  
A6, B5: 500 sheets

Paper Type: Thin, Plain, Recycled,  
Heavy, Color, Bond, Transparency\*,  
Envelope <sup>\*14</sup>

Staple Paper Weight: 60 to 120g/m<sup>2</sup>  
Staple Position: Corner  
Staple Paper Size: A4, Custom size  
(210.0 x 279.4 mm to 216.0 x 355.6  
mm)  
Staple Capacity: 30 sheets (60 to  
90g/m<sup>2</sup>), 20 sheets (91 to 120g/m<sup>2</sup>)

## Hardware Accessories



### Card Readers

Copy Card Reader-F1  
Copy Card Reader Attachment-B5

## Security Options



### Device Security

iR-ADV Security Kit-AR1 for IEEE  
2600 Common Criteria Certification  
(available at a later date)

## System and Controller Options



### Print Accessories

PCL International Font Set-A1  
PCL Asian Font Set-A1

### Barcode Printing

Barcode Printing Kit-D1

### System Accessories

Copy Control Interface Kit-A1  
Connection Kit-A2 for Bluetooth LE  
NFC Kit-E1

**Fax Accessories**

Super G3 FAX Board-AT1  
Remote Fax Kit-A1  
IP FAX Expansion Kit-B1

**Other Options****Accessibility Accessories**

ADF Access Handle-A1

**Consumables**

Staple-P1

1. A different initial HDD may be used.
2. Available with upper tray.
3. Time from device power-on to when the copy icon appears and is enabled to operate on the touch panel display.
4. Time from device power on, until copy ready (not print reservation).
5. Optional PCL International Font Set-A1 is required.
6. Optional Barcode Printing Kit-D1 is required.
7. 1-sided.
8. Detect Feeder Multi Sheet Feed is supported.
9. Sent as A4.
10. 1 Requires uniFLOW Online / uniFLOW.
11. Reference value: measured one unit.
12. 1.0 W is not available in all circumstances due to certain settings.
13. Paper capacity may vary with different paper type/size.
14. Only for Main Unit Output tray.

- Prices, specifications, availability and terms of offers may change without notice.
- Products / Services may be manufactured by and/or supplied to us by third party manufacturers / suppliers for distribution / resale (non-Canon brand products).
- Prices above are maximum retail price (MRP) and may change without prior notice.

Copyright © 2023 Canon India Pvt Ltd. All rights reserved.